



WPC

Classic LED Wall Pack

WPC	-	-	-	-	-	W	-
	Wattage	Voltage	Lens	CCT	Mounting	Options	
40W	40W / 4,284lm	LV = 120-240 VAC	G = Borosilicate Glass	40K = 4000K	W = Wall Mount		
60W	60W / 7,908lm	HV = 277-480 VAC	P = High-Impact Polycarbonate	50K = 5000K			
80W	80W / 10,407lm						
120W	120W / 14,304lm						

OPERATION

Array Lifetime	100,000+ Hours
Driver Lifetime	50,000 Hours
Voltage	120 - 240 VAC 277-480 VAC (Optional)
Operating Temperature	-40°C to 40°C
Optimal Temperature	-40°C to 35°C
Power Factor	> 0.90
Frequency	50/60 Hz
Colour Rendering Index	80

CERTIFICATIONS

Locations	Suitable for wet or dry locations
CSA Standards	CSA C22.2 No.250.0-08
UL Standards	UL 1598 (Edition 3) UL 8750 (Edition 1): 2009

CONSTRUCTION

Housing	Powder Coated Cast Aluminum
Lens	Borosilicate Glass High Impact Polycarbonate
Optic	90° x 120°
Enclosure Rating	IP65
Dimensions (L x H x D)	366mm x 231mm x 222mm 14.4" x 9.1" x 8.7"
Weight	3.8 kg / 8.3 lbs

