

LHB

Linear LED High Bay Light



LHB	Wattage	Voltage	Optic	CCT	Mounting	Options
	90W = 90W / 14,850lm	LV = 120-277 VAC	4012 = 40° x 120°	40K = 4000K	C = Cable Suspension	DI = Dimming
	120W = 120W / 19,800lm	HV = 277-480 VAC	3070 = 30° x 70°	50K = 5000K	S = Surface Mount	O = Occupancy Sensor
	150W = 150W / 24,750lm		5090 = 50° x 90°			DS = Daylight Sensor
	180W = 180W / 29,700lm		120D = 120°			

OPERATION

Array Lifetime	100,000+ Hours
Driver Lifetime	50,000 Hours
Voltage	120 - 277 VAC
Operating Temperature	-40°C to 50°C
Optimal Temperature	-40°C to 35°C
Power Factor	> 0.93
Frequency	50/60 Hz
Colour Rendering Index	>70 (>80 Optional)

CERTIFICATIONS

Locations	Suitable for wet or dry locations
CSA Standards	CSA C22.2 No.250.0-08
UL Standards	UL 1598 (Edition 3) UL 8750 (Edition 1): 2009

CONSTRUCTION

Housing	Powder Coated Aluminum
Lens	Polycarbonate
Enclosure Rating	IP65
Dimensions (L x W x H) [mm]	90W: 718 x 137 x 102 - 4.7kg 120W: 948 x 137 x 102 - 5.7kg 150W: 1178 x 137 x 102 - 7.0kg 180W: 718 x 275 x 102 - 8.5kg

90W



120W



150W



180W

