

EXL

Class I & II LED Light



EXL	-	-	110D	-	-	-
	Wattage	Voltage	Optic	CCT	Mounting	Options
	20W (2') = 20W / 2,800lm	LV = 120-277 VAC	110D = 110°	30K = 3000K	U = U-Bracket	WG = Wire Guard
	40W (2') = 40W / 5,600lm	HV = 277-480 VAC		40K = 4000K		CLA = CH Lid Adaptor
	40W = 40W / 5,600lm			50K = 5000K		
	60W = 60W / 8,400lm					
	80W = 80W / 11,200lm					

OPERATION

Array Lifetime	100,000+ Hours
Driver Lifetime	50,000 Hours
Voltage	120 - 277 VAC 277 - 480 VAC
Operating Temperature	-40°C to 50°C
Optimal Temperature	-40°C to 35°C
Power Factor	> 0.95
Frequency	50/60 Hz
Colour Rendering Index	>80

CERTIFICATIONS

Locations	Suitable for wet or dry locations
CSA Standards	CSA C22.2 No.250.0 CSA C22.2 No.137.0
UL Standards	UL 1598 UL 8750 UL 844
Hazardous Locations	Class I, Div. 2, Groups A, B, C, D Class II, Div. 1, Groups E, F, G Class II, Div. 2, Groups F, G Class III

CONSTRUCTION

Housing	Cast Aluminum	
Lens	Tempered Glass	
Enclosure Rating	IP66	
Dimensions (L x H x D)	20W 40W	650mm x 130mm x 205mm 25.6" x 5.1" x 8.1"
	40W 60W 80W	1,299mm x 130mm x 205mm 51.1" x 5.1" x 8.1"

