



WPU

Universal LED Wall Pack

WPU	40-120	UV		50K	W	
	Adjustable Wattage	Voltage	Lens	CCT	Mounting	Options
	33% = 40W / 5,752lm	UV = 120-347 VAC	G = Borosilicate Glass P = High-Impact Polycarbonate	50K = 5000K	W = Wall Mount	
	50% = 60W / 8,627lm					
	66% = 80W / 11,500lm					
	83% = 100W / 14,379lm					
	100% = 120W / 17,255lm					

OPERATION

Array Lifetime	100,000+ Hours
Driver Lifetime	50,000 Hours
Voltage	120 - 347 VAC
Operating Temperature	-40°C to 40°C
Optimal Temperature	-40°C to 35°C
Power Factor	> 0.90
Frequency	50/60 Hz
Colour Rendering Index	80

CERTIFICATIONS

Locations	Suitable for wet or dry locations
CSA Standards	CSA C22.2 No.250.0-08
UL Standards	UL 1598 (Edition 3) UL 8750 (Edition 1); 2009

CONSTRUCTION

Housing	Powder Coated Cast Aluminum
Lens	Borosilicate Glass High Impact Polycarbonate
Optic	110°
Enclosure Rating	IP65
Dimensions (L x H x D)	365mm x 237mm x 187mm 14.4" x 9.3" x 7.4"
Weight	3.6 kg / 7.9 lbs

