



# FLDM

Compact LED Flood Light

FLDM	50-70	UV	90D	ACT		
	Adjustable Wattage	Voltage	Optic	Adjustable CCT	Mounting	Options
	70% = 49W / 6,370lm	UV = 120-347 VAC	90D = 90° x 120°	3000K	U = U-Bracket S = Slip-Fit Adaptor	
	80% = 56W / 7,280lm			4000K		
	90% = 63W / 8,190lm			5000K		
	100% = 70W / 9,100lm					

## OPERATION

Array Lifetime	100,000+ Hours
Driver Lifetime	50,000 Hours
Voltage	120 - 347 VAC
Operating Temperature	-40°C to 50°C
Optimal Temperature	-40°C to 35°C
Power Factor	> 0.93
Frequency	50/60 Hz
Colour Rendering Index	>80

## CERTIFICATIONS

Locations	Suitable for wet or dry locations
CSA Standards	CSA C22.2 No.250.0-08
UL Standards	UL 1598 (Edition 3) UL 8750 (Edition 1): 2009

## CONSTRUCTION

Housing	Powder Coated Cast Aluminum
Lens	Polycarbonate
Enclosure Rating	IP65
Dimensions (L x H x D)	265mm x 233mm x 57mm 10.4" x 9.2" x 2.2"
Weight	3.0 kg 6.8 lbs

