



WPA

Architectural LED Wall Pack

WPA	-	-	-	90D	-	40K	-	W	-	-
		Wattage		Optic		CCT		Mounting		Options
		12W = 12W / 1,285lm		90D = 90° x 120°		40K = 4000K		W = Wall Mount		
		30W = 30W / 3,239lm								
		50W = 50W / 5,193lm								
		80W = 80W / 9,056lm								
		120W = 120W / 13,796lm								
			LV = 120-277 VAC							
			HV = 347 VAC							

OPERATION

Array Lifetime	100,000+ Hours
Driver Lifetime	50,000 Hours
Voltage	120 - 277 VAC 347 VAC (Optional)
Operating Temperature	-40°C to 40°C
Optimal Temperature	-40°C to 35°C
Power Factor	0.93
Frequency	50/60 Hz
Colour Rendering Index	83.5

CERTIFICATIONS

Locations	Suitable for wet or dry locations
CSA Standards	CSA C22.2 No.250.0-08
UL Standards	UL 1598 (Edition 3) UL 8750 (Edition 1): 2009

CONSTRUCTION

Housing	Powder Coated Cast Aluminum
Lens	Polycarbonate
Enclosure Rating	IP65
Dimensions (L x H x D) [mm]	12W: 127 x 150 x 86 - 0.9kg 30W: 193 x 228 x 114 - 2.0kg 50W: 193 x 228 x 114 - 2.0kg 80W: 281 x 334 x 138 - 4.8kg 120W: 281 x 334 x 138 - 4.8kg

