



BL620

Class 2 LED Bay Light

BL620	-	LV	-	-	-	U	-	
Wattage		Voltage		Optic		CCT	Mounting	Options
160W = 176W / 19,000lm		LV = 120-277 VAC		60D = 60°		30K = 3000K	U = U-Bracket	
200W = 220W / 22,000lm				90D = 90°		40K = 4000K		
				120D = 120°		50K = 5000K		

OPERATION

Array Lifetime	100,000+ Hours
Driver Lifetime	50,000 Hours
Voltage	120 - 277 VAC
Operating Temperature	-40°C to 50°C
Optimal Temperature	-40°C to 35°C
Power Factor	> 0.98
Frequency	50/60 Hz
Colour Rendering Index	>70

CERTIFICATIONS

Locations	Suitable for wet or dry locations
CSA Standards	CSA C22.2 No.250.0-08 CSA C22.2-137-M1981 (R2004)
UL Standards	UL 1598 (Edition 3) UL 8750 (Edition 1): 2009
Hazardous Locations	Class II, Div. 2, Groups E, F, G Class III

CONSTRUCTION

Housing	Zinc-Coated Cast Aluminum
Lens	Tempered Glass - Frosted
Enclosure Rating	IP65
Dimensions (Diameter x H)	ø 529 mm x 319 mm ø 20.8" x 12.6"
Weight	22.2 kg 48.8 lb

