



EXP200

Class 1 LED Light

EXP200	Wattage	LV	Optic	CCT	U	Options
	20W = 20W / 1,925lm	LV = 120-277 VAC	60D = 60°	30K = 3000K	U = U-Bracket	
	30W = 30W / 2,888lm		90D = 90°	40K = 4000K		
	40W = 40W / 3,850lm		120D = 120°	50K = 5000K		
			140D = 140°	65K = 6500K		

OPERATION

Array Lifetime	100,000+ Hours
Driver Lifetime	50,000 Hours
Voltage	120 - 277 VAC
Operating Temperature	-40°C to 50°C
Optimal Temperature	-40°C to 35°C
Power Factor	> 0.95
Frequency	50/60 Hz
Colour Rendering Index	>70

CERTIFICATIONS

Locations	Suitable for wet or dry locations
CSA Standards	CSA C22.2 No.250.0-08 CSA C22.2-137-1981 (R2004)
UL Standards	UL 1598 (Edition 3) UL 8750 (Edition 1): 2009 UL 844 (Edition 12)
Hazardous Locations	Class I, Div. 2, Groups A, B, C, D Class II, Div. 1, Groups E, F, G Class III

CONSTRUCTION

Housing	Cast Aluminum w/ Anti-Static, Anti-Corrosion Coating
Lens	Tempered Glass - Frosted
Enclosure Rating	IP66
Dimensions (L x H x D)	200 mm x 200 mm x 202 mm 7.9 " x 7.9 " x 8.0 "
Weight	4.0 kg 8.8 lb

