



WPR

Rotatable LED Wall Pack

WPR	Wattage	LV	60D	CCT	W	Options
	25W = 25W / 3,280lm	LV = 120-277 VAC	60D = 60°	40K = 4000K 50K = 5000K	W = Wall Mount	
	40W = 40W / 5,131lm					
	60W = 60W / 7,853lm					
	80W = 80W / 10,598lm					

OPERATION

Array Lifetime	100,000+ Hours
Driver Lifetime	50,000 Hours
Voltage	120 - 277 VAC
Operating Temperature	-30°C to 45°C
Optimal Temperature	-30°C to 35°C
Power Factor	0.94
Frequency	50/60 Hz
Colour Rendering Index	73

CERTIFICATIONS

Locations	Suitable for wet or dry locations
CSA Standards	CSA C22.2 No.250.0-08
UL Standards	UL 1598 (Edition 3) UL 8750 (Edition 1): 2009

CONSTRUCTION

Housing	Anodized Cast Aluminum
Lens	Polycarbonate
Enclosure Rating	IP65
Dimensions (L x H x D) [mm]	25W: 231 x 133 x 137 - 1.9kg 40W: 231 x 133 x 137 - 2.0kg 60W: 234 x 135 x 221 - 3.0kg 80W: 234 x 135 x 221 - 3.0kg



25W
40W

60W
80W

